

### Product type designation

### CM 1243-5

COMMUNICATION MODULE CM 1243-5 FOR CONNECTION OF SIMATIC S7-1200 TO PROFIBUS AS DP MASTER MODULE; PG/OP COMMUNICATION; S7-COMMUNICATION



### Transmission rate

#### Transfer rate

- at the 1st interface / acc. to PROFIBUS

9.6 kbit/s ... 12 Mbit/s

### Interfaces

Number of interfaces / acc. to Industrial Ethernet

0

Number of electrical connections

- at the 1st interface / acc. to PROFIBUS
- for power supply

1

1

Type of electrical connection

- at the 1st interface / acc. to PROFIBUS
- for power supply

9-pin Sub-D socket (RS485)

3-pole terminal block

### Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / external

24 V

Supply voltage / external / at DC / Rated value

24 V

Relative positive tolerance / at DC / at 24 V

20 %

Relative negative tolerance / at DC / at 24 V

20 %

|  |       |
|--|-------|
| Consumed current   |       |
| <ul style="list-style-type: none"> <li>from external supply voltage / at DC / at 24 V / typical</li> </ul> | 0.1 A |
| Power loss [W]   | 2.4 W |

### Permitted ambient conditions

|  |                |
|--|----------------|
| Ambient temperature  |                |
| <ul style="list-style-type: none"> <li>for vertical installation / during operation</li> </ul>         | 0 ... 45 °C    |
| <ul style="list-style-type: none"> <li>for horizontally arranged busbars / during operation</li> </ul> | 0 ... 55 °C    |
| <ul style="list-style-type: none"> <li>during storage</li> </ul>                                       | -40 ... +70 °C |
| <ul style="list-style-type: none"> <li>during transport</li> </ul>                                     | -40 ... +70 °C |
| Relative humidity / at 25 °C / without condensation / during operation / maximum                       | 95 %           |
| Protection class IP  | IP20           |

### Design, dimensions and weight

|   |                                     |
|---|-------------------------------------|
| Module format   | Compact module S7-1200 single width |
| Width   | 30 mm                               |
| Height  | 100 mm                              |
| Depth   | 75 mm                               |
| Net weight  | 0.134 kg                            |
| Mounting type   |                                     |
| <ul style="list-style-type: none"> <li>35 mm DIN rail mounting</li> </ul> | Yes                                 |
| <ul style="list-style-type: none"> <li>S7-300 rail mounting</li> </ul>    | No                                  |
| <ul style="list-style-type: none"> <li>wall mounting</li> </ul>           | Yes                                 |

### Product properties, functions, components / general

|   |   |
|---|---|
| Number of units   |   |
| <ul style="list-style-type: none"> <li>per CPU / maximum</li> </ul> | 3 |

### Performance data / PROFIBUS DP

|   |          |
|---|----------|
| Service / as DP master  |          |
| <ul style="list-style-type: none"> <li>DPV1</li> </ul>  | Yes      |
| Number of DP slaves / on DP master / usable   | 16       |
| Amount of data  |          |
| <ul style="list-style-type: none"> <li>of the address area of the inputs / as DP master / total</li> </ul>  | 512 byte |
| <ul style="list-style-type: none"> <li>of the address area of the outputs / as DP master / total</li> </ul> | 512 byte |
| <ul style="list-style-type: none"> <li>of the address area of the inputs / per DP slave</li> </ul>          | 244 byte |
| <ul style="list-style-type: none"> <li>of the address area of the outputs / per DP slave</li> </ul>         | 244 byte |
| <ul style="list-style-type: none"> <li>of the address area of the diagnostic data / per DP slave</li> </ul> | 240 byte |
| Service / as DP slave   |          |

- DPV0 No
- DPV1 No

### Performance data / S7 communication

- Number of possible connections / for S7 communication
- maximum 8
  - with PG connections / maximum 1
  - with PG/OP connections / maximum 3
  - Note max. 4 connections to other S7 stations

### Performance data / multi-protocol mode

- Number of active connections / with multi-protocol mode
- without DP / maximum 8
  - with DP / maximum 8

### Performance data / telecontrol

- Protocol / is supported
- TCP/IP No

### Accessories

### Further Information / Internet Links

- Internet-Link
- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
  - to website: Industrial communication <http://www.siemens.com/simatic-net>
  - to website: Industry Mall <https://mall.industry.siemens.com>
  - to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
  - to website: Image database <http://automation.siemens.com/bilddb>
  - to website: CAx Download Manager <http://www.siemens.com/cax>
  - to website: Industry Online Support <https://support.industry.siemens.com>

### Security information

---

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

11/13/2017