


Plexo™

complete surface-mounting IP 55



Pack	Cat.Nos	Switches 10 AX - 250 V~
10 5	0 697 11 0 697 16	IP 55 – IK 07 Automatic terminals ● Grey Two-way switch Intermediate switch
10	0 697 12	Two-way switch with indicator Supplied with 230 V~ lamp
5	0 697 13	Illuminated two-way switch Supplied with 230 V~ lamp
10	0 697 15	Two-gang two-way switch
1	0 697 17	Double pole switch
Push-buttons 10 A		
10	0 697 20	IP 55 – IK 07 Automatic terminals ● Grey N/O contact
10	0 697 22	Illuminated N/O contact Supplied with 230 V~ lamp
Movement detectors		
1 1	0 697 80 0 697 40	IP 55 - IK 04 Automatic terminals Allows control of a lighting device as soon as the movement is detected Maximum load: - 2000 W for incandescent and halogen lamps 230 V~ and - 2000 W for ELV halogen lamps, - 1000 VA for fluorescent tubes and compact fluorescent lamps Detection range from 0 to 12 m Detection angle : 360° Coverage pattern adjustable during installation process Temporization between 12 s and 16 min. Dim. 90x90x85 mm ○ White ● Grey

Pack	Cat.Nos	Socket outlets
10	0 697 33	● Grey German standard 16 A – 250 V~ 2P+E with earth lateral contact screw terminals
10	0 697 32	British standard 13 A – 250 V~ 2P+E with screw terminals
5	0 697 39	2 x 2P+E screw terminals
5	0 697 50	2P+E unswitched + switch screw terminals
10	0 697 31	French standard 16 A – 250 V~ 2P+E with shutters for child protection, automatic terminals
Socket outlets 20 and 32 A		
Screw terminals ● Grey		
20 A - IP 55 - IK 08 Compatible with membrane glands Cat.No 0 919 14		
5	0 916 55	2P+E - 230 V~
5	0 916 56	3P+E - 230 V~
5	0 916 57	3P+N+E - 230 V~
32 A - IP 44 - IK 08 Compatible with membrane glands Cat.No 0 919 15		
5	0 558 72	2P+E - 230 V~
5	0 558 75	3P+E - 230 V~
5	0 558 77	3P+N+E - 230 V~
Membrane glands with marking of Ø for tubes and cables		
50	0 919 14	Grey (RAL 7035) Up to Ø20
50	0 919 15	Up to Ø25